

产品及应用/products applications

- ◆

机床控制变压器是参考德国西门子公司样机制造的新产品，符合VDE0550、IEC204-1、IEC439、GB5226-85等有关国际、国家标准。机床控制变压器适用于在交流50Hz-60Hz，输入额定电压不大于500V，额定输出电压不大于220V，作为各行业的机械设备，一般电器的控制电源和工作照明、信号灯的电源之用

◆

The machine tool control transformer is a new product manufactured by referencing the samples of Siemens AG, Germany. It complies with relevant international and national standards such as VDE0550, IEC204-1, IEC439, and GB5226-85. The machine tool control transformer is suitable for use as a control power source for various industries' mechanical equipment and general electrical appliances, as well as a power source for work lighting and signal lamps, with an AC frequency of 50Hz-60Hz, an input rated voltage not exceeding 500V, and an output rated voltage not exceeding 220V.
-
- 技术参数/Specification
1. 额定容量： 25VA~5000VA

2.输入电压： 380V 220V 110V

3.环境温度： -15℃~+40℃

4.工频耐压： 3KV/min

5.输出电压： 6V/6.3V/12V/24V/36V/48V/110V/127V/220V/380V

1. Rated capacity: 25VA~5000VA

2.Input voltage: 380V 220V 110V

3.Ambient temperature: -15℃~+40℃

4.Power frequency withstand voltage: 3KV/min

5.Output voltage: 6V/6.3V/12V/24V/36V/48V/11V/127V/220V/380V
- | 变压器型号 | 容量
VA | 重量
kg | 外形尺寸 | | | 安装尺寸 | | 安装孔 |
|-----------|----------|----------|------|-----|-----|---------|---------|--------|
| | | | L | W | H | A | B | |
| JBK3-40 | 40 | 1.2 | 78 | 72 | 89 | 56±0.4 | 51±2.5 | 4.8×9 |
| JBK3-50 | 50 | 1.3 | 78 | 72 | 89 | 56±0.4 | 51±2.5 | 4.8×9 |
| JBK3-63 | 63 | 1.3 | 78 | 72 | 89 | 56±0.4 | 51±2.5 | 4.8×9 |
| JBK3-80 | 80 | 1.8 | 84 | 105 | 94 | 64±0.4 | 66±2.5 | 4.8×9 |
| JBK3-100 | 100 | 2.1 | 84 | 105 | 94 | 64±0.4 | 66±2.5 | 4.8×9 |
| JBK3-125 | 125 | 2.5 | 96 | 105 | 109 | 84±0.4 | 71±3 | 5.8×11 |
| JBK3-160 | 160 | 2.8 | 96 | 105 | 109 | 84±0.4 | 71±3 | 5.8×11 |
| JBK3-200 | 200 | 3.2 | 96 | 120 | 109 | 84±0.4 | 86±3 | 5.8×11 |
| JBK3-250 | 250 | 3.5 | 96 | 120 | 109 | 84±0.4 | 86±3 | 5.8×11 |
| JBK3-315 | 315 | 4.4 | 120 | 109 | 123 | 90±0.4 | 90±2 | 7×12 |
| JBK3-400 | 400 | 4.9 | 120 | 109 | 123 | 90±0.4 | 90±2 | 7×12 |
| JBK3-500 | 500 | 6.2 | 150 | 112 | 150 | 122±0.5 | 90±3.5 | 7×12 |
| JBK3-630 | 630 | 7.2 | 150 | 112 | 150 | 122±0.5 | 90±3.5 | 7×12 |
| JBK3-800 | 800 | 10 | 160 | 210 | 151 | 126±2 | 152±2 | 7×12 |
| JBK3-1000 | 1000 | 12.5 | 160 | 210 | 151 | 126±2 | 152±2 | 7×12 |
| JBK3-1250 | 1250 | 15.2 | 184 | 235 | 163 | 146±3.5 | 176±3.5 | 7×12 |
| JBK3-1600 | 1600 | 21.5 | 184 | 235 | 163 | 146±3.5 | 176±3.5 | 7×12 |
| JBK3-2000 | 2000 | 25.5 | 210 | 265 | 171 | 174±3.5 | 200±3.5 | 7×12 |
| JBK3-2500 | 2500 | 28 | 210 | 265 | 171 | 174±3.5 | 200±3.5 | 7×12 |
- 备注： 以上为我司标准规格，特殊规格可根据客户要求定制.
-
-